

# CT-40

## FEATURES

- Heavy Duty – Over 4500 PSI
- Corrosion Inhibitor Included
- Portland Cement Based
- One Component – Just Add Water
- Shrinkage-Compensated
- Polymer Modified
- Custom Colors Available



## WHERE TO USE

- Featheredge to over 2" thick
- Patch Concrete and Mortar
- Resurface Concrete
- Interior or Exterior Surfaces
- Horizontal, Vertical or Overhead
- Warehouse Floors, Bridges
- Beams, Columns or Balconies
- Full Depth Repairs when Extended

**CT-40  
DRY LATEX MORTAR**

**CT-40 Dry Latex Mortar** is a 1 component, polymer modified, high performance concrete repair and resurfacing mortar. **CT-40 Dry Latex Mortar** is simply mixed with water and applied from featheredge to over 2" thick in one application. Apply horizontal, vertical or overhead. Product sets in 20 to 45 minutes and ready for light traffic in 3 to 4 hours at 70 degrees Fahrenheit.

### Product Description

**CT-40 Dry Latex Mortar** is a special blend of cements, aggregates and exclusive modifiers. Designed for general purpose and high performance concrete repair or resurfacing applications.

### CT-40 Packaging and Yield

50 lb. Heavy-duty polyethylene bag: .42 cubic feet

### For Best Results

Apply to a clean, dry sound substrate above 40° F Rub or scratch part of the mixed material onto surface just prior to application. Do not allow rub or scratch coat to dry before application. Check moisture content (mat test) prior to applying any waterproof topping. Do not retemper already mixed material.

### Technical Data

Compressive strength	28 day	Exceeds 4500 psi	ASTM C42
Compressive strength	7 day	Exceeds 3000 psi	ASTM C42
Compressive strength	1 day	Exceeds 2500 psi	ATSM C42
Flexural strength	28 day	Exceeds 800 psi	ASTM C78
Freeze / Thaw Durability:		Excellent	ASTM C666
Bond Strength		Exceeds 150 psi	ACI 503 R
Color:		Concrete Gray	
Working Time:		15-30 Minutes	

Reasonable variations for the above data can be expected depending on field conditions, surface preparation, curing, contractor expertise and evaluation and/or handling of test cylinders. Contact JE Tomes for additional details

### Surface Preparation

Surface preparation is critical to achieve long lasting results. Existing concrete surface shall be clean, sound, and free of oil, grease, laitance, curing compounds, or any other foreign substance. Areas treated with product must be free of dust and any foreign matter prior to topping application. On highly porous substrates, contact the manufacturer for recommended application procedures.

### Mixing Guidelines

Approximately 3-4 quarts of water is required to mix 50 lb of product for patching applications. Always add and mix product into water. For applications 1.5" to 2" or more, extend product up to 40% with clean and dry 3/8" pea gravel.

### Application

Trowel apply. Rub or scratch part of the mixed material onto surface just prior to application.

### Curing

Rapid drying of cement-based products may cause cracking or de-bonding. Avoid applications in high winds, excessive heat or blowing air directly on freshly place product. If these conditions apply, damp cure for 1-3 days. Curing compounds, wet burlap or polyethylene will reduce rapid drying but may cause color change or mar product surface. Allow 3-4 hours for light traffic on horizontal repairs. Contact JE Tomes if you have any questions or concerns with your application.



**JE Tomes & Associates, Inc.**  
2513 West 140<sup>th</sup> Place, Blue Island, IL. 60406

**Telephone: 708-653-5100**

Toll free: 877-JETOMES

Fax: 708-653-5101

**Rock Solid Products Since 1935**

**A-7**

#### LIMITED WARRANTY

JE Tomes & Associates, Inc. warrants its products to be free from manufacturing defects, and will deliver, at no charge, an equal amount of packaged product as that amount proven to be defective when applied in accordance with manufacturer's written directions by contractors experienced in this application, and used in applications recommended by the manufacturer as suitable for the product. All claims concerning product defects must be made within twelve (12) months of use of the product. THERE ARE NO OTHER WARRANTIES BY JE TOMES & ASSOCIATES, INC. OF ANY NATURE WHATSOEVER, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IN CONNECTION WITH PRODUCTS WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. Buyer's sole and exclusive remedy for breach of any warranty shall be replacement of defective product. JE Tomes & Associates, Inc. shall not be liable for any damages, including consequential damages, except as otherwise set forth therein.