

CONCRETE & PLASTER BOND	FEATURES
	<ul style="list-style-type: none"> <li>▪ Easy to Mix and Apply</li> <li>▪ Long Lasting Formula</li> <li>▪ Will not re-emulsify</li> <li>▪ Breathable</li> <li>▪ Highly Versatile</li> <li>▪ Self-Bonding/Self-Curing</li> <li>▪ Water will not affect the dry bond</li> <li>▪ Chemical Resistant</li> </ul>

WHERE TO USE
<ul style="list-style-type: none"> <li>▪ Indoors or Outdoors</li> <li>▪ Where Added Durability is Required</li> <li>▪ Bonding New Concrete to Old</li> <li>▪ Plaster Bonding or Primer</li> </ul>

**CONCRETE & PLASTER BOND** is a special water-based bonding agent designed to improve bonding for cement-based toppings, patches, stucco, plasters, gypsum and masonry. Once Concrete & Plaster Bond dries clear topping can be applied same day or up to 3 days later.

**Product Description**

**Concrete & Plaster Bond** is a special water-base bonding agent designed to improve bonding for cement-based toppings, patches, stucco, plasters, gypsum and masonry. Once Concrete & Plaster Bond dries clear topping can be applied same day or up to 3 days later.

**Concrete & Plaster Bond Packaging and Yield**

**Concrete & Plaster Bond** is available in quarts, gallon jugs, 5 gallon pails and 55 gallon drums.

Amount	Coverage (Concrete)	Coverage (Plaster)
1 Gallon	Up to 150 ft. <sup>2</sup>	Up to 300 ft. <sup>2</sup>

**For Best Results**

Apply to a clean, dry sound substrate above 50° F. Check moisture content (mat test) prior to applying any waterproof topping. Do not retemper already mixed material. Do not expose to rain or flowing water during application. **Concrete & Plaster Bond** is to be stored in a dry, cool place. Do not allow product to freeze.

<b>Technical Data</b>		
Tensile bond strength (3 day)	487 psi	ASTM C932
Vibration testing	various toppings	Excellent
<b>Failure occurred in topping – no bond line failure</b>		

**Surface Preparation**

Surface preparation is critical to achieve long lasting results. Existing concrete substrate shall be clean, sound, and free of oil, grease, laitance, curing compounds, or any other foreign matter. Areas treated with product must be free of dust and any foreign matter prior to topping application. On highly porous substrates, contact the manufacturer for recommended application procedures.

**Application**

**Concrete & Plaster Bond** has a milky white appearance. Allow product to dry clear before topping.

**Curing**

Avoid applications in high winds, excessive heat or blowing air directly on freshly place product. Contact JE Tomes if you have any questions or concerns with your application.

**WARNING**

**KEEP OUT OF REACH OF CHILDREN.** If eaten or swallowed, serious personal injury could occur. Prolonged contact with skin may cause irritation. In case of eye contact, flood eyes repeatedly with water. Consult your physician under any of the above circumstances.



**JE Tomes & Associates, Inc.**  
 2513 West 140<sup>th</sup> Place, Blue Island, IL. 60406  
**Telephone: 708-653-5100**  
 Toll free: 877-JETOMES  
 Fax: 708-653-5101



**Rock Solid Products Since 1935**

**LIMITED WARRANTY**

JE Tomes & Associates, Inc. warrants its products to be free from manufacturing defects, and will deliver, at no charge, an equal amount of packaged product as that amount proven to be defective when applied in accordance with manufacturer's written directions by contractors experienced in this application, and used in applications recommended by the manufacturer as suitable for the product. All claims concerning product defects must be made within twelve (12) months of use of the product. THERE ARE NO OTHER WARRANTIES BY JE TOMES & ASSOCIATES, INC. OF ANY NATURE WHATSOEVER, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IN CONNECTION WITH PRODUCTS WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. Buyer's sole and exclusive remedy for breach of any warranty shall be replacement of defective product. JE Tomes & Associates, Inc. shall not be liable for any damages, including consequential damages, except as otherwise set forth therein.