

## DRY FAST SET

## FEATURES

- Polymer Modified
- Portland Cement Based
- Self-Curing, Self-Bonding
- Waterproof Underlayment
- Short Setting Time – Under an Hour
- One Component – Just Add Water
- Custom Colors Available



## WHERE TO USE

- Smoothing and Filling Depressions
- Featheredge to Over 1" Thick
- On Concrete, Wood, Plywood, Ceramic
- Used on naval vessels
- Underlayment for Tile & Carpet
- Over Waterproof Cutback Adhesive
- Driveways, Sidewalks
- Interior or Exterior

**DRY FAST SET**  
LATEX LIQUID FLOOR

**Dry Fast Set Latex Liquid Floor** is a 1 component, polymer modified, high performance repair and resurfacing mortar. **Dry Fast Set Latex Liquid Floor** is simply mixed with water and applied to concrete, wood, plywood or ceramic from featheredge to over 1" thick in one application. Apply horizontal, vertical or overhead. Apply with trowel, Brush or Broom. Product sets in 20 to 45 minutes and ready for light traffic in 3 to 4 hours at 70 degrees Fahrenheit.

### Product Description

**Dry Fast Set Latex Liquid Floor** is a special blend of cement, aggregate and exclusive modifiers. Designed for general purpose and high performance concrete repair or resurfacing applications.

### Dry Fast Set Packaging and Yield

40 lb. Bag (Troweled): 40 sq. feet @ 1/8"  
40 lb. Bag (Brush/Broom): up to 300 sq. feet

### For Best Results

Apply to a clean, dry sound substrate above 40° F. Rub or scratch part of the mixed material onto surface just prior to application. Do not allow rub or scratch coat to dry before application. Check moisture content (mat test) prior to applying any waterproof topping. Do not retemper already mixed material.

### Technical Data

|                           |        |                  |           |
|---------------------------|--------|------------------|-----------|
| Compressive strength      | 28 day | Exceeds 4500 psi | ASTM C42  |
| Compressive strength      | 7 day  | Exceeds 3000 psi | ASTM C42  |
| Compressive strength      | 1 day  | Exceeds 2500 psi | ASTM C42  |
| Freeze / Thaw Durability: |        | Excellent        | ASTM C666 |
| Bond Strength             |        | Exceeds 150 psi  | ACI 503 R |
| Color:                    |        | Concrete Gray    |           |

Reasonable variations for the above data can be expected depending on field conditions, surface preparation, curing, contractor expertise and evaluation and/or handling of test cylinders. Contact JE Tomes for additional details

#### LIMITED WARRANTY

JE Tomes & Associates, Inc. warrants its products to be free from manufacturing defects, and will deliver, at no charge, an equal amount of packaged product as that amount proven to be defective when applied in accordance with manufacturer's written directions by contractors experienced in this application, and used in applications recommended by the manufacturer as suitable for the product. All claims concerning product defects must be made within twelve (12) months of use of the product. THERE ARE NO OTHER WARRANTIES BY JE TOMES & ASSOCIATES, INC. OF ANY NATURE WHATSOEVER, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IN CONNECTION WITH PRODUCTS WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. Buyer's sole and exclusive remedy for breach of any warranty shall be replacement of defective product. JE Tomes & Associates, Inc. shall not be liable for any damages, including consequential damages, except as otherwise set forth therein.

### Surface Preparation

Surface preparation is critical to achieve long lasting results. Existing concrete surface shall be clean, sound, and free of oil, grease, laitance, curing compounds, or any other foreign substance. Areas treated with product must be free of dust and any foreign matter prior to topping application. On highly porous substrates, contact the manufacturer for recommended application procedures.

### Mixing Guidelines

Approximately 1 gallon (4 quarts) of water is required to mix 40 lb of product for troweling. Rub or scratch mixed material onto surface just prior to application. For brush or broom applications, 2 gallons of water is required, and force action mixing is recommended. For uniform finish, apply with brush or broom in same direction.

### Application

Trowel, brush or broom apply to clean surface. Rub or scratch part of the mixed material onto surface just prior to application.

### Curing

Avoid applications in high winds, excessive heat or blowing air directly on freshly place product. Product sets in 20-45 minutes. Allow 3-4 hours for light traffic on horizontal repairs. Contact JE Tomes if you have any questions or concerns with your application.



**JE Tomes & Associates, Inc.**

2513 West 140<sup>th</sup> Place, Blue Island, IL. 60406

Telephone: 708-653-5100

Toll free: 877-JETOMES

Fax: 708-653-5101

**Rock Solid Products Since 1935**

**A-3**