

GUN-RITE SUPERFLO	FEATURES	WHERE TO USE	GUN-RITE SUPERFLO
	<ul style="list-style-type: none"> ▪ Proven “Gun-Rite” Admixture ▪ Lowers water / Cement Ratio ▪ Increases Slump Life ▪ Compatible with most concrete mixes ▪ Compatible with All Gun-Rite Shotcrete ▪ Compatible with most shotcrete mixes 	<ul style="list-style-type: none"> ▪ Bridge Repairs ▪ Parking Garage Restoration ▪ Interior or Exterior Surfaces ▪ Wastewater Tanks ▪ Slope Stabilization ▪ Mines or Manholes 	

Gun-Rite SuperFlo is a highly concentrated liquid plasticizing admixture that allows for easier pumping and flow capability. **Gun-Rite SuperFlo** increases strength development, slump life and reduces water demand.

Product Description

Gun-Rite SuperFlo is a Superplasticizing liquid blend that allows for greater pumping capability, increased strength development, slump life and reduces water demand. Designed for general-purpose and high performance shotcrete and concrete applications.

GUN-RITE SuperFlo Packaging

GUN-RITE SuperFlo is packaged in 5-gallon pails or 55-gallon drums.

For Best Results

Apply Concrete or Gun-Rite enhanced shotcrete above 40° F. Follow ACI guidelines for preparation, shooting and curing. Do not let product freeze.

Recommended Dosage

Recommended dosage is 5 -20 ounces per 100 lb. of cement or up to 2 oz. Per bag of Gun-Rite 5000. Job conditions may vary the recommended dosage slightly, Start with lower dosages and increase as needed. If other dosages are required, contact JE Tomes / US Shotcrete, Inc. for assistance.

Compatibility

GUN-RITE SuperFlo is compatible with all Gun-Rite shotcrete enhancers and Gun-Rite prepackaged shotcrete mixes. Gun-Rite SuperFlo is also compatible with most conventional and high performance shotcrete and concrete mixes.

Applicable Standards

Type F Water Reducing ASTM C 494,
High range admixture and upper range for type G
Water reducing and retarding admixture

LIMITED WARRANTY

JE Tomes & Associates, Inc. warrants its products to be free from manufacturing defects, and will deliver, at no charge, an equal amount of packaged product as that amount proven to be defective when applied in accordance with manufacturer's written directions by contractors experienced in this application, and used in applications recommended by the manufacturer as suitable for the product. All claims concerning product defects must be made within twelve (12) months of use of the product. THERE ARE NO OTHER WARRANTIES BY JE TOMES & ASSOCIATES, INC. OF ANY NATURE WHATSOEVER, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IN CONNECTION WITH PRODUCTS WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. Buyer's sole and exclusive remedy for breach of any warranty shall be replacement of defective product. JE Tomes & Associates, Inc. shall not be liable for any damages, including consequential damages, except as otherwise set forth therein.



JE Tomes & Associates, Inc.

2513 West 140th Place, Blue Island, IL. 60406

Telephone: 708-653-5100

Toll free: 877-JETOMES

Fax: 708-653-5101

Rock Solid Products Since 1935