

JETASEAL

FEATURES

- Prevents Deterioration
- Protects Against Water and Salts
- A Treatment – 100% Breathable
- Not a surface sealer – Deep Penetrating
- Easy to Use – Attach Hose and Spray
- Available in Quarts and ½ Gallons

WHERE TO USE

- Bridges
- Highways
- Airport Runways
- Stadiums
- Balconies
- Parking Garages

JETASEAL

Penetrating Treatment for Concrete & Masonry

Product Description

JETASEAL is a commercial-grade water repellent concentrate. Designed for protection of surfaces of all types.

JETASEAL Packaging and Yield

Concentrate Amount	Amount Yielded	Coverage
1 Quart	2.5 Gallons	250-500 sq. ft.

Coverage will depend on porosity of concrete

For Best Results

Apply to a clean, dry sound substrate above 40° F. Do not retemper already mixed material. Do not expose to rain or flowing water during application.

Technical Data

Depth of Penetration:	Up to 1/8 Inch
Vapor Permeability:	100%
Moisture Resistance:	Excellent
Skid Resistance:	No Change
Color:	No Color Change

LIMITED WARRANTY

JE Tomes & Associates, Inc. warrants its products to be free from manufacturing defects, and will deliver, at no charge, an equal amount of packaged product as that amount proven to be defective when applied in accordance with manufacturer's written directions by contractors experienced in this application, and used in applications recommended by the manufacturer as suitable for the product. All claims concerning product defects must be made within twelve (12) months of use of the product. THERE ARE NO OTHER WARRANTIES BY JE TOMES & ASSOCIATES, INC. OF ANY NATURE WHATSOEVER, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IN CONNECTION WITH PRODUCTS WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. Buyer's sole and exclusive remedy for breach of any warranty shall be replacement of defective product. JE Tomes & Associates, Inc. shall not be liable for any damages, including consequential damages, except as otherwise set

forth therein.

Surface Preparation

Surface preparation is critical to achieve long lasting results. Existing concrete substrate shall be clean, sound, and free of oil, grease, laitance, curing compounds, or any other foreign matter. Substrate must be able to allow material to penetrate

Application

Connect to water hose in off position. Start water hose flow. Direct nozzle to concrete and or masonry surface to be treated. Turn nozzle to ON position. Generously spray concrete or masonry surface. Properly mixed material is opaque, dries clear.

Curing

Avoid applications in high winds, excessive heat or blowing air directly on freshly place product. Cont JE Tomes if you have any questions or concerns with your application.



JE Tomes & Associates, Inc.

2513 West 140th Place, Blue Island, IL. 60406

Telephone: 708-653-5100

Toll free: 877-JETOMES

Fax: 708-653-5101

Rock Solid Products Since 1935

D-1

Updated: 4/11