

LATEX LIQUID FLOOR

FEATURES

- Waterproof Underlayment
- Just Add Latex Liquid
- Shrinkage-Compensated
- Portland Cement Based
- High Performance – Over 7,000 psi

WHERE TO USE

- Smoothing and Filling Depressions
- On Concrete, Wood, Plywood, Ceramic
- Featheredge to 1/4" Thick
- Underlayment for Tile & Carpet
- Over Waterproof Cutback Adhesive
- Driveways, Sidewalks
- Interior or Exterior

LATEX LIQUID
FLOOR

Latex Liquid Floor is a high performance underlayment and resurfacing mortar. **Latex Liquid Floor** is mixed with Latex Liquid and applied from featheredge to 1/4" thick in one application. Product sets overnight and is ready for light traffic in 12 to 24 hours at 70 degrees Fahrenheit.

Product Description

Latex Liquid Floor is a special blend of cement, aggregate and exclusive modifiers. Designed for general purpose and high performance concrete repair or resurfacing applications.

Latex Liquid Floor Packaging and Yield

40 lb. Heavy-duty polyethylene bag: 40 sq. ft. @ 1/8"

For Best Results

Apply to a clean, dry sound substrate above 40° F. Rub or scratch part of the mixed material onto surface just prior to application. Do not allow rub or scratch coat to dry before application. Check moisture content (mat test) prior to applying any waterproof topping. Do not retemper already mixed material.

Technical Data

Compressive strength	28 day	Exceeds 7000 psi	ASTM C109
Compressive strength	14 day	Exceeds 5600 psi	ASTM C109
Flexural strength	28 day	Exceeds 600 psi	ASTM C78
Bond Strength		Exceeds 200 psi	ACI 503 R
Color:		Light Concrete Gray	

Reasonable variations for the above data can be expected depending on field conditions, surface preparation, curing, contractor expertise and evaluation and/or handling of test cylinders. Contact JE Tomes for additional details

Surface Preparation

Surface preparation is critical to achieve long lasting results. Existing concrete surface shall be clean, sound, and free of oil, grease, laitance, curing compounds, or any other foreign substance. Areas treated with product must be free of dust and any foreign matter prior to topping application. On highly porous substrates, contact the manufacturer for recommended application procedures.

Mixing Guidelines

Approximately 1 gallon of Latex Liquid is required to mix 40 lb of dry product. Always add and mix product into Latex Liquid.

Application

Trowel apply. For all applications, rub or scratch mixed material onto surface just prior to application.

Curing

Rapid drying of cement-based products may cause cracking or de-bonding. Avoid applications in high winds, excessive heat or blowing air directly on freshly place product. Product sets overnight and is ready for light traffic in 12 to 24 hours at 70 degrees Fahrenheit. Contact JE Tomes if you have any questions or concerns with your application.

LIMITED WARRANTY

JE Tomes & Associates, Inc. warrants its products to be free from manufacturing defects, and will deliver, at no charge, an equal amount of packaged product as that amount proven to be defective when applied in accordance with manufacturer's written directions by contractors experienced in this application, and used in applications recommended by the manufacturer as suitable for the product. All claims concerning product defects must be made within twelve (12) months of use of the product. THERE ARE NO OTHER WARRANTIES BY JE TOMES & ASSOCIATES, INC. OF ANY NATURE WHATSOEVER, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IN CONNECTION WITH PRODUCTS WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. Buyer's sole and exclusive remedy for breach of any warranty shall be replacement of defective product. JE Tomes & Associates, Inc. shall not be liable for any damages, including consequential damages, except as otherwise set forth therein.



JE Tomes & Associates, Inc.

2513 West 140th Place, Blue Island, IL. 60406

Telephone: 708-653-5100

Toll free: 877-JETOMES

Fax: 708-653-5101

Rock Solid Products Since 1935

B-2

Updated: 4/11