

QUICK FLOOR AND WALL PATCH

FEATURES

- Quick Setting – Under an Hour
- Portland Cement and Gypsum Based
- One or Two Component
- Shrinkage-Compensated

WHERE TO USE

- Smoothing and Leveling Floors & Walls
- Concrete, Particle Board, Wood
- Above Grade Only
- Smooth Concrete & Ceramics
- Interior Applications Only

QUICK FLOOR AND WALL PATCH

QUICK FLOOR & WALL PATCH is a 1 or 2 component patching & resurfacing product. **QUICK FLOOR & WALL PATCH** is simply mixed with water or latex liquid and applied from 1/16" to over 3" thick in one application. Apply horizontal, vertical or overhead. Product sets in 20 to 45 minutes and ready for light traffic in 1 to 2 hours at 70 degrees F.

Product Description

QUICK FLOOR & WALL PATCH is a special blend of cements, aggregate and exclusive modifiers designed for ultimate workability in one application. Use to quickly patch & resurface concrete, concrete block, ceramic, plywood, particle board and other sound surfaces indoors and above grade.

Packaging and Yield

QUICK FLOOR & WALL PATCH is packaged in 25lb bags and. A 25 lb. unit of product will yield 25 square feet at 1/8".

For Best Results

Apply to a clean, dry sound substrate above 40° F. Check moisture content (mat test) prior to applying any waterproof topping. Do not retemper already mixed material. Do not expose to rain or flowing water during application.

Technical Data

Compressive strength	7 day	Exceeds 2300 psi	ASTM C39
Compressive strength	28 day	Exceeds 2500 psi	ASTM C39

Reasonable variations for the above data can be expected depending on field conditions, surface preparation, curing, contractor expertise and evaluation and/or handling of test cylinders. Contact JE Tomes for additional details

LIMITED WARRANTY

JE Tomes & Associates, Inc. warrants its products to be free from manufacturing defects, and will deliver, at no charge, an equal amount of packaged product as that amount proven to be defective when applied in accordance with manufacturer's written directions by contractors experienced in this application, and used in applications recommended by the manufacturer as suitable for the product. All claims concerning product defects must be made within twelve (12) months of use of the product. THERE ARE NO OTHER WARRANTIES BY JE TOMES & ASSOCIATES, INC. OF ANY NATURE WHATSOEVER, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IN CONNECTION WITH PRODUCTS WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. Buyer's sole and exclusive remedy for breach of any warranty shall be replacement of defective product. JE Tomes & Associates, Inc. shall not be liable for any damages, including consequential damages, except as otherwise set forth therein.

Surface Preparation

Surface preparation is critical to achieve long lasting results. Existing surface shall be clean, sound, and free of oil, grease, laitance, curing compounds, or any other foreign substance. Areas treated with product must be free of dust and any foreign matter prior to topping application. On highly porous substrates, contact the manufacturer for recommended application procedures. Apply to a clean, dry sound substrate above 40° F.

Mixing Guidelines

Always add and mix product into water or Latex Liquid. Rub or scratch mixed material onto surface just prior to application. *Mix with Latex Polymer liquid for applications over wood surfaces or to increase bond strengths on other substrates.*

Application

Apply from 1/16" to over 3" thick in one application.

Curing

Rapid drying of cement-based products may cause cracking or de-bonding. Avoid applications in high winds, excessive heat or blowing air directly on freshly place product. Curing compounds, wet burlap or polyethylene will reduce rapid drying but may cause color change or mar product surface. If form is used, allow material to cure in form for 2 or more days before removing forms. Allow one day for light traffic on horizontal repairs. Contact JE Tomes if you have any questions or concerns with your application.



JE Tomes & Associates, Inc.

2513 West 140th Place, Blue Island, IL. 60406

Telephone: 708-653-5100

Toll free: 877-JETOMES

Fax: 708-653-5101

Rock Solid Products Since 1935

A-6