SUPERSMOOTH FEATURES

- Fast Setting
- Polymer Modified
- Easy to Apply
- Portland Cement Based
- One Component – Just Add Water
- Super Fine Finish – Trowels Like Butter

WHERE TO USE

- Sound Substrates up to ½" Thick
- Over Concrete, Wood, Ceramic
- Over Linoleum or Wood Seam
- On top of Waterproof Adhesives
- Areas Exposed to Water
- Horizontal, Vertical or Overhead
- Interior or Exterior as Wearing Surface

SUPERSMOOTH EMBOSSER

SuperSmooth Embosser is a 1 component, polymer modified, high performance Cement-Based resurfacing mortar. **SuperSmooth Embosser** is simply mixed with water and applied over concrete, wood, ceramic, or linoleum from featheredge to 1/2" thick in one application. Apply horizontal, vertical or overhead. Product sets in 20 to 45 minutes and ready for light traffic in 1 to 4 hours at 70 degrees Fahrenheit**. Unique formulation allows for use interior, exterior or areas exposed to water.** Product can be used over any bonded waterproof adhesives.

Product Description

SuperSmooth Embosser is a special blend of cements, fine aggregates and exclusive modifiers. Designed for general-purpose and high performance resurfacing applications.

SuperSmooth Packaging and Yield

15 lb. bag: Approx. 35 sq. ft. @ 1/16"

For Best Results

Apply to a clean, dry sound substrate above 40° F
Rub or scratch part of the mixed material onto surface just prior to application. Do not allow rub or scratch coat to dry before application. Check moisture content (mat test) prior to applying any waterproof topping. Do not retemper already mixed material.

Technical Data

Compressive strength	28 day	Exceeds 4000 psi	ASTM C42
Compressive strength	7 day	Exceeds 3000 psi	ASTM C42
Compressive strength	1 day	Exceeds 2500 psi	ASTM C42
Flexural Strength:	28 day	Exceeds 1000 psi	ASTM C78
Freeze / Thaw Durability:		Excellent	ASTM C666
Bond Strength		Exceeds 150 psi	ACI 503 R
Color:		Concrete Gray	

Reasonable variations for the above data can be expected depending on field conditions, surface preparation , curing, contractor expertise and evaluation and/or handling of test cylinders. Contact JE Tomes for additional details

LIMITED WARRANTY
JE Tomes & Associates, Inc. warrants its products to be free from manufacturing defects, and will deliver, at no charge, an equal amount of packaged product as that amount proven to be defective when applied in accordance with manufacturer's written directions by contractors experienced in this application, and used in applications recommended by the manufacturer as suitable for the product. All claims concerning product defects must be made within twelve (12) months of use of the product. THERE ARE NO OTHER WARRANTIES BY JE TOMES & ASSOCIATES, INC. OF ANY NATURE WHATSOEVER, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IN CONNECTION WITH PRODUCTS WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. Buyer's sole and exclusive remedy for breach of any warranty shall be replacement of defective product. JE Tomes & Associates, Inc. shall not be liable for any damages, including consequential damages, except as otherwise set forth therein.

Surface Preparation

Surface preparation is critical to achieve long lasting results. Existing concrete surface shall be clean, sound, and free of oil, grease, laitance, curing compounds, or any other foreign substance. Areas treated with product must be free of dust and any foreign matter prior to topping application. On highly porous substrates, contact the manufacturer for recommended application procedures.

Mixing Guidelines

Up to 3 quarts of water is required to mix 15 lb. of product. Always add and mix product into water. Hold back 1 part water, mix for 2-3 minutes and adjust at final mixing stage to desired consistency.

Application

Trowel apply from featheredge to ½" thick.

Curing

Rapid drying of cement-based products may cause cracking or de-bonding. Avoid applications in high winds, excessive heat or blowing air directly on freshly place product. AFTER APPLICATION WAIT 2 TO 6 HOURS (depending on thickness and conditions) PRIOR TO FLOOR COVERING Contact JE Tomes if you have any questions or concerns with your application.

JE Tomes & Associates, Inc.
2513 West 140th Place, Blue Island, IL. 60406
Telephone: 708-653-5100
Toll free: 877-JETOMES
Fax: 708-653-5101
Rock Solid Products Since 1935