



# JETaFLOW™ Primer

## Primer for JETaFLOW self leveling topping

### Repair Thickness

5 to 10 mils

### Set Time

45 minutes

### Application Technique

Broom

### Where to Use

- Indoors or outdoors
- Primer for JETaFLOW self leveling
- Bonding new concrete to old

### Features

- Easy to mix and apply
- Long lasting formula
- Will not re-emulsify
- Water will not affect the dry bond
- Self-bonding/self-curing
- Breathable

### Packaging and Yield

1 gal                      Up to 150 sq ft  
*5 gal pails and 55 gal drums  
also available*

### Product Description

**JETaFLOW Primer** is a special water-base primer / bonding agent designed to improve bonding and flow for **JETaFLOW** self-leveling topping. Once **JETaFLOW Primer** dries clear (approximately 1 to 2 hours) topping can be applied up to 3 days later.

### For Best Results

Apply to a clean, dry sound substrate above 50° F. Check moisture content (mat test) prior to applying any waterproof topping. Do not retemper already mixed material. Do not expose to rain or flowing water during application. **JETaFLOW Primer** is to be stored in a dry, cool place. Do not allow product to freeze.

### Surface Preparation

Surface preparation is critical to achieve long lasting results. Existing concrete substrate shall be clean, sound, and free of oil, grease, laitance, curing compounds, or any other foreign matter. Areas treated with product must be free of dust and any foreign matter prior to topping application. On highly porous substrates, contact the manufacturer for recommended application procedures.

### JETaFLOW Primer Application

Broom apply onto surface taking care to avoid puddling. **JETaFLOW Primer** has a milky white appearance. Allow to dry clear (approximately 1 to 2 hours) prior to **JETaFLOW** application. If applied product accumulates dust or debris before topping is applied, reapply **JETaFLOW Primer** or product effectiveness will be significantly reduced.

### Curing

Rapid drying of product may cause cracking or de-bonding. Avoid applications in high winds, excessive heat, or blowing air directly on freshly placed product. Allow one to two hours for product to dry. Contact JE Tomes if you have any questions or concerns with your application.

### Warning

**KEEP OUT OF REACH OF CHILDREN.** If eaten or swallowed, serious personal injury could occur. Prolonged contact with skin may cause irritation. In case of eye contact, flood eyes repeatedly with water. Consult your physician under any of the above circumstances.

### LIMITED WARRANTY

JE Tomes & Associates, Inc. warrants its products to be free from manufacturing defects and will deliver, at no charge, an equal amount of packaged product as that amount proven to be defective when applied in accordance with manufacturer's written directions by contractors experienced in this application, and used in applications recommended by the manufacturer as suitable for the product. All claims concerning product defects must be made within twelve (12) months of use of the product. THERE ARE NO OTHER WARRANTIES BY JE TOMES & ASSOCIATES, INC. OF ANY NATURE WHATSOEVER, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE IN CONNECTION WITH PRODUCTS WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. Buyer's sole and exclusive remedy for breach of any warranty shall be replacement of defective product. JE Tomes & Associates, Inc. shall not be liable for any damages, including consequential damages, except as otherwise set forth therein.