

## 1) Chemical Product and Company Identification

## **Product details:**

Manufacturer/Supplier:	JE Tomes & Associates, Inc. Blue Island, IL 60406 Phone: (800) 538-6637 Fax: (708) 653-5101 www.jetomes.com
Trade Name and Synonyms:	CT-40 Do All Mortar, CT-40
Product Description:	Concrete repair mortar, patching mortar

## 2) Hazardous Identifications

## According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

### **Classification of the Product**

2
1
3 (irritating to respiratory system)
1 (by inhalation)

Skin corrosion/irritation Serious eye damage/eye irritation Specific target organ toxicity - single exposure Specific target organ toxicity - repeated exposure

## Label elements



Signal Word:

	V
-	
Danger	

Hazard Statement:	
H318	Causes serious eye damage.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H372	Causes damage to organs (Lung) through prolonged or repeated exposure (inhalation).

Precautionary Statements (Prevention):

- Wear protective gloves and eye/face protection. P289
- Use only outdoors or in a well-ventilated area. P271
- P260 Do not breathe dust/gas/mist/vapors.
- Do not eat, drink or smoke when using this product. P270
- Wash with plenty of water and soap thoroughly after handling. P264

Precautionary Statements (Response):

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P303+P352	IF ON SKIN (or hair): Wash with plenty of soap and water.
P362+P364	Take off contaminated clothing and wash before reuse.

# Safety Data Sheet: CT-40 Do All Mortar

Revision Date: 05/27/2015



Precautionary Stateme	nts (Storage):	
P403+P233	Store in a well-ventilated place.	Keep container tightly closed.
P405	Store locked up.	

Precautionary Statements (Disposal): P501 Dispose of contents/container to hazardous or special waste collection point.

### Hazards not otherwise classified

If applicable, information is provided in this section on other hazards which to not result in classification, but which may contribute to the overall hazards of the substance or mixture.

## 3) Composition/Information on Ingredients

## According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

CAS #	Component	Percent	
65997-15-1	Portland cement	15 - 50	
65997-16-2	Calcium Aluminate Cement	0.1 - 20	
14808-60-7	Crystalline silica	45 - 95	
24937-78-8	Vinyl acetate copolymer	1 – 15	

Note: Exact percentages of ingredients have been withheld as a trade secret in accordance with OSHA

## 4) First Aid Measures

### General Advice

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

### First Aid: Eyes

Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists, get medical attention.

### First Aid: Skin

Flush with large amounts of water. Do not use organic solvents. If irritation persists, get medical attention.

### First Aid: Ingestion

If material is ingested, immediately contact a physician or poison control center. Drink plenty of water and flush out mouth with water. Do not induce vomiting, unless instructed by poison control center or doctor.

### First Aid: Inhalation

Immediately remove the affected person to fresh air. If symptoms persist, seek medical attention.

### First Aid: Notes to Physician

Provide general supportive measures and treat symptomatically.

## 5) Fire-Fighting Measures and Fire Hazards

### **Extinguishing Media**

Foam, water spray, dry powder, carbon dioxide

### **Unsuitable Extinguishing Media**

Water jet (for safety reasons)

### **Additional Information:**

Product is non-combustible. Packaging materials can catch fire. The extinguishing agents normally used are sufficient.



### Special hazards arising from the substance or mixture

Hazards during fire-fighting: Carbon monoxide, carbon dioxide, harmful vapors Evolution of fumes/fog. The substances/groups of substances mentioned can released in case of fire. Product is not combustible or explosive.

### Advice for fire-fighters

Protective equipment for fire-fighting: Wear self-contained breathing apparatus and chemical-protective clothing.

### Further information:

Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered. The degree of risk is governed by the burning substance and the fire conditions. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

## 6) Accidental Release Measures (Spills or Leaks)

### **Personal Precautions**

Avoid the generation of dusts during clean-up. Avoid contact with skin and eyes. Wear appropriate protective equipment and clothing during clean-up.

## **Containment Procedures**

Contain the discharged material.

### **Environmental Precautions**

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations. Do not discharge into drains/surface waters/groundwater.

#### **Clean-Up Procedures**

Attempt to reclaim the free product, if this is possible. Shovel the material into waste container. Thoroughly wash the area with water after a spill or leak clean-up. Wear appropriate protective equipment and clothing during clean-up. Keep out of the reach of children.

### Evacuation Procedures

None identified.

### Special Procedures

Wear a dust mask if dust is generated above exposure limits.

## 7) Handling and Storage

### Handling Procedures

Avoid dust formation. The Cement contained in this product reacts alkaline when in contact with water or humidity. This may cause severe irritation of skin or mucous membranes. The humidity of the skin or mucous membranes is enough for this reaction. Prolonged direct contact to the dry product should be avoided therefore. Avoid inhalation of dusts. Avoid skin contact. Pour downwind and allow as little free fall as possible when emptying bags into equipment. Breathing must be protected when large quantities are decanted without local exhaust ventilation.

Protection against fire and explosion: No special precautions necessary.

### Conditions for safe storage, including any incompatibilities



Segregate from metals. Segregate from acids. Segregate from lyes, Segregate from oxidants. Segregate from foods and animal feeds.

Suitable materials for containers: tinned carbon steel (Tinplate)

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

## 8) Exposure Controls, Personal Protection

## COMPONENT EXPOSURE LIMITS

Portland Cement (65997-15-1)

ACGIH:	1 mg/m3 TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)
OSHA:	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)

### Calcium Aluminate Cement (65997-16-2)

ACGIH:	3 mg/m3 TWA (respirable particles); 10 mg/m3 TWA (inhalable particles)
OSHA:	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)

### Crystalline Silica (14808-60-7)

ACGIH:	0.025 mg/m3 TWA (respirable fraction)
OSHA:	0.1 mg/m3 TWA (respirable dust)

### Vinyl Acetate Copolymer (24937-78-8)

ACGIH:	10 mg/m <sup>3</sup> (Total dust); 3 mg/m <sup>3</sup> (respirable fraction)
OSHA:	15 mg/m <sup>3</sup> (Total dust); 5 mg/m <sup>3</sup> (respirable fraction)

### **Engineering Controls**

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits. Local exhaust is suggested for use, where possible, in enclosed or confined spaces.

## PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Wear safety glasses with side shields or goggles.

### Personal Protective Equipment: Skin

The use of nitrile-latex gloves is recommended

### Personal Protective Equipment: Respiratory

If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.

### **Personal Protective Equipment: General**

Launder contaminated clothing before reuse. Use good industrial hygiene practices in handling this material.

### General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. Avoid inhalation of dusts. In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks). Contaminated equipment or clothing should be cleaned after each use or disposed of.

## 9) Physical and Chemical Properties

Form:

powder

# Safety Data Sheet: CT-40 Do All Mortar

Revision Date: 05/27/2015



Odor: Odor threshold:	odorless	Not determined due to potential health hazard by inhalation.
Color pH value: Melting point: Boiling point:	gray	neutral to slightly alkaline Unspecified N/A
Sublimation point: Flash point:	N/A	The substance/product is non-combustible
Flammability: Lower explosion limit:	not determined	As a result of our experience with this product and our knowledge of its composition, we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.
Upper explosion limit:		As a result of our experience with this product and our knowledge of its composition, we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.
Autoignition: Vapor Pressure: Density:		N/A N/A N/A
Relative density: Bulk density:	2.8 1,800-2,400 kg/m3	
Vapor density:	1,800-2,400 kg/m3	N/A
Partitioning coefficient n-octanol/water (low Pow):		N/A
Self-ignition temperature: Thermal decomposition		not self-igniting No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic:		N/A
Viscosity, kinematic:		N/A Product has not been tested.
Solubility in water: Solubility (quantitative):		N/A
Solubility (qualitative):		N/A
Evaporation Rate Other information:		N/A If necessary, information on other physical and chemical parameters is indicated in this section.

## 10) Stability and Reactivity

## Reactivity

No hazardous reactions if stored and handle as prescribed/indicated.

### Oxidizing properties:

Based on its structural properties, the product is not classified as oxidizing.

## **Chemical Stability**

The product is stable if stored and handled as prescribed/indicated.

## Possibility of hazardous reactions

The product is stable if store and handles as prescribed/indicated. Strong bases are formed on the addition of water.

## Conditions to avoid

Avoid dust formation. Avoid humidity.



## Incompatible materials

Strong bases, strong acids

## Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition: No decomposition of stored and handled as prescribed/indicated.

## **11)** Toxicological Information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

### Acute Toxicity/Effects

### Acute toxicity

Assessment of acute toxicity: Product may present a nuisance dust hazard. Inhalation of dust may cause respiratory tract irritation, coughing and breathing difficulties.

<u>Oral</u> N/A

Inhalation N/A

<u>Dermal</u> N/A

### **Chronic Toxicity/Effects**

### Repeated dose toxicity

Assessment of repeated dose toxicity: This product contains crystalline silica (quartz). Prolonged or repeated inhalation of respirable crystalline silica may result in silicosis.

### Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available data, the classification criteria are not met.

### Carcinogenicity

Exposure to quarts (the most stable and common form of crystalline silica) is responsible for the majority of clinically diagnosed silicosis. Silicosis in a fibronodular lung disease that occurs after occupational exposure to crystalline silica for 5 years or longer. Inhalation of quartz dusts may cause shortness of breath, limitation of chest expansion, dry cough, and a lessened capacity for work. Individuals with a pre-existing disease in, or a history of ailments involving the skin or respiratory tract, are at a greater risk of developing adverse health effects when exposed to this material. There may be a relationship between silicosis and certain cancers.

### Reproductive toxicity

Assessment of reproductive toxicity: The chemical structure does not suggest a specific alert for such an effect. Based on available data, the classification criterial are not met.



## Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available data, the classification criterial are not met.

### Other information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

### Sensitization

No information available for the product.

## 12) Ecological Information

### Toxicity

<u>Aquatic toxicity</u> Assessment of aquatic toxicity: There is a high probability that the product is not acutely harmful to aquatic organisms. The product gives rise to pH shifts. Based on available data, the classification criteria are not met.

### Persistence and degradability

### Assessment of biodegradation and elimination (H20)

Inorganic product which cannot be eliminated from water by biological purification processes. The product is slightly soluble in water. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.

Experience shows this product to be inert and non-degradable.

Elimination information: N/A

### Bioaccumulative potential

<u>Assessment of bioaccumulation potential</u> The product will not be readily bioabailable due to its consistency and insolubility in water.

## Mobility in soil

## Assessment of transport between environmental compartments

The substance will not evaporate into the atmosphere from the water surface. Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater is not expected.

## Additional Information

Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

## 13) Disposal Considerations

## US EPA Waste Number & Descriptions A: General Product Information

No additional information available.

# Safety Data Sheet: CT-40 Do All Mortar

Revision Date: 05/27/2015



## **B: Component Waste Numbers**

No EPA Waste Numbers are applicable for this product's components.

### **Disposal Instructions**

Waste must be handled in accordance with all federal, state, provincial, and local regulations. Consult authorities before disposal.

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

## 14) Transportation Information

## **International Transportation Regulations**

Not regulated as dangerous goods.

## **15) Regulatory Information**

### **US Federal Regulations**

All of the components of this product are listed on, or are exempted from listing on the U.S. EPA TSCA Inventory of Chemical Substances. All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List unless otherwise noted.

### **State Regulations**

The following statement(s) are provided under the California State Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains a chemical known to the state of California to cause cancer. This product contains a chemical know to the state of California to cause reproductive/developmental effects.

### **NFPA Hazard codes:**

Health: 3 Fire: 0 Reactivity: 0 Special:

## 16) Other Information

**Disclaimer:** Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial and local laws.